Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Waveguide Directional Coupler

WR-2.2/WR-2.2/10dB Coupling

Model: TC-330500-10-2.2

TC-330500-10-2.2 is a three-port waveguide directional coupler that delivers a 10 dB nominal coupling level and 25 dB typical directivity across the full waveguide band from 330 to 500 GHz. The interfaces of the directional coupler are WR-2.2 waveguides with UG-387/U anti-cocking flanges.

Features:

- Operating Frequency 330 to 500GHz
- Full Band Operation
- Low Insertion Loss
- Moderate Directivity

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	330		500	GHz
Insertion Loss		3		dB
Coupling		10		dB
Coupling Accuracy		±2		dB
Isolation		35		dB
Directivity		25		dB
Main Line VSWR		1.1		:1
Coupling Port VSWR		1.1		:1


Envrionmental And Physical Characteristics:

Parameter	Value	Units
Operating Temerature	-40 To +85	℃
Storage Temerature	-40 to +85	℃
RF Connectors	WR-2.2/UG-387/U	
Coupled Port	WR-2.2/UG-387/U	
Size	36*22*23	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TC-330500-10-2.2	Waveguide Directional Coupler, 330-500GHz, Coupling:10dB Typ, WR-2.2/UG-387/U	Rev.1.0